



Searchlight Type: SEEMATZ EFA463LED24220WB			Date:
Drawn: M. Vink TTTBV	Approved:	Sign:	 THEUNISSEN <small>TECHNICAL TRADING BV</small>
Theunissen Technical Trading BV PB 70 6580 AB Malden Tel. +31-(0)24 3584455 Fax +31-(0)24 3582166 www.tttbv.nl			



Datasheet Searchlight



Type: EFA463LED24220WB

Electrical data: 24V 220W Wide beam

Construction features :

Case and bows consist of seawater resistant aluminium. Non-magnetic aluminium of type AlMg3 is used. All other metal parts are made of stainless steel or brass. All coloured parts are powder coated.

Front Pane:

Hardened glas, resistant to temperature changes

Sealing:

Seal for front Pane: silicone square gasket
Seal for plug-in unit: square cord foam rubber

Electrical Equipment:

LED Lamp 220W
Electronic thermostat +30°C
Connection Cable for heating silicone cable

Technical data lamp:

Power 110VA
Voltage 24VDC
Current consumption 1,1A
Light output 35900lm
Average burning life 50.000 Hours

Searchlight:

DIN-Range at 1 Lux 1100m
IES-Range at 1Lux 1250m
Angle of light beam 11,0 °
Light spot size at target 210m
Protective System IP 56
Operating temperature -10°C - + 40°C
Swiveling time horizontal approx 20 sec for 330°
Swiveling time vertical approx 45 sec for 60°
Lamp socket type Cree XP-G3
Connection cable 3m, type 3x 1,5mm²
Weight complete searchlight 57Kg

Motor control:

Power cons. searchlight and remote control 510VA
Voltage 24VDC
Fuse T6.3A
Power consumption of motors max. 100VA

Can be used with max. 1 operator panels:

EFCPA 144 x 72mm